



# BLO19 2000 >80

BLO192000024DC15320840000W05

Article no.: 101132

**BILTON**  
FOCUSED  
ON  
LINEAR  
LIGHT




Lamp voltage



Luminous flux per meter



Max. length




Colour rendering index CRI

## TENDER TEXT

BILTONONE 2000 LED strip 24VDC 15,3W/m IP20 CRI>80 4000K WHITE 5m LED module BLO19 2000 >80 Article 101132 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LED dimmer. Suitable for ambient temperatures from -20 ... +45 °C at a service life of 60000 h . The BLO19 2000 >80 LED-strip has a luminous flux of 2000 lm at 15.3 W, resulting in an efficiency of 131 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 7000.0 mm can be achieved. In terms of lighting, the module has a colour temperature of 4000 K and a beam angle of 120°. All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 7.14 mm. Degree of protection IP20 Dimension (L x W x H): 5000.0 mm x 8.0 mm x 1.5 mm

## TOP-FEATURES

- //\_\_ Improvement of homogeneity by 20 additional LEDs per meter
- //\_\_ Wide choice of light colors and lumen packages
- //\_\_ Wide range of applications for linear lighting in white
- //\_\_ With a maximum module length of up to 7000.0 mm long, linear lighting lines can be implemented



# BLO19 2000 >80

**BLO192000024DC15320840000W05**

Article no.: 101132

## MECHANICAL DATA

Net width [mm]	8.0
Net height [mm]	1.5
Net length [mm]	5000.0
Degree of protection (IP)	IP20
Colour	White
Net weight [g]	49
Distance [mm]	7.14
Distance relating to	LED to LED
Length of particular segments [mm]	50.0

## ELECTRICAL DATA

Overall efficiency [lm/W]	131
Lamp power per meter [W]	15.3
Lamp voltage [V]	24
Input voltage range [V]	23 - 25
Voltage type	DC
Protection class	III

## LIGHT TECHNICAL DATA

Luminous flux per meter [lm]	2000
Beam angle [°]	120
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	>80
Colour temperature [K]	4000
Energy efficiency class provided exchangeable built-in lamp	A +

## CONNECTION

Number of poles	2
Conductor cross section [mm²]	0.50
Max. length [mm]	7000.0

## TEMPERATURE TECHNICAL DATA

Rated life time L80/B10 at 25 °C [h]	60000
Ambient temperature during operating [°C]	- 20 ... + 45
Ambient/storage temperature [°C]	- 5 ... + 55
Operation temperature at Tc [°C]	- 5 ... + 60

## PACKAGING INFORMATION

EAN	4250716934236
-----	---------------

**BLO192000024DC15320840000W05**

Article no.: 101132

Article no.	101132
Customs tariff number	94054099
Length [mm]	5000.0
Gross weight [g]	175.0
Gross height [mm]	18.0
Gross width [mm]	200.0
Gross length [mm]	200.0
State of origin	AT

\* Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.biltingroup.com](http://www.biltingroup.com)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.biltingroup.com](http://www.biltingroup.com)